



APP 120.305 Eelde Approach

TWR 118.705 Eelde Tower
119.705

ATIS 133.555 Eelde Information
121.500 General Emergency

TRANSITION LEVEL BY ATC
TRANSITION ALTITUDE 3000 ft AMSL

DO NOT DESCEND BELOW THE DESCENT PROFILE

- Missed Approach:
- Track 051° MAG and climb to 2000 ft AMSL.
Inform ATC.
- Missed Approach in case of communication failure:
- Track 051° MAG and climb to 3000 ft AMSL;
- When passing 2000 ft AMSL start a left turn to 320° MAG;
- When reaching 3000 ft AMSL proceed to VZ;
- After arriving over VZ hold or descend to 2000 ft AMSL in an outbound turn, intercept final approach and execute the instrument approach procedure again.

THR ELEV 13

DIST RELATED TO EEL DME

GS IN KT	60	80	100	120	140	160	180
VERTICAL SPEED	320 ft/min	425 ft/min	530 ft/min	635 ft/min	745 ft/min	850 ft/min	955 ft/min

OCA (OCH) ELEV THR 05: 13.3 ft

MSA BASED ON EEL VOR/DME

ACFT CAT	VOR MAPT: THR	CIRCLING*	* Circling approaches shall be executed south-east of the AD, unless otherwise instructed by ATC.	THR 05 53°06'40"N 006°33'39"E EH511 53°02'52"N 006°25'47"E
A	440 (420)	450 (430)		
B		520 (500)		
C		620 (600)		
D		840 (830)		
CEILING AND VISIBILITY MINIMA				BEARINGS ARE MAGNETIC DISTANCES IN NM ALTITUDES AND ELEVATIONS IN FEET
TAKE-OFF	DAY:	NIGHT:		
LANDING	DAY: NA	NIGHT: NA		

NOTED ON FILE VOR/DME

