


- Missed Approach:
 - Track 231° MAG and climb to 2000 ft AMSL. Inform ATC.
- Missed Approach in case of communication failure:
 - Track 231° MAG and climb to 3000 ft AMSL;
 - When passing 2000 ft AMSL start a right turn to 320° MAG;
 - When reaching 3000 ft AMSL proceed to S0;
 - After arriving over S0 hold or descend to 2000 ft AMSL in an outbound turn, intercept final approach and execute the instrument approach procedure again.

DO NOT DESCEND BELOW THE DESCENT PROFILE

TRANSITION LEVEL BY ATC
TRANSITION ALTITUDE 3000 ft AMSL

ACFT CAT	CAT I	LOC MAPt: THR	CIRCLING*
A	161 (148)	430 (420)	450 (430)
B	174 (161)		520 (500)
C	184 (171)		620 (600)
D	197 (184)		840 (830)

* Circling approaches shall be executed south-east of the AD, unless otherwise instructed by ATC.

THR 23 53°07'30"N 006°35'25"E
EH512 53°11'15"N 006°43'23"E

CEILING AND VISIBILITY MINIMA			
TAKE-OFF	DAY:	NIGHT:	
LANDING	DAY: NA	NIGHT: NA	

BEARINGS ARE MAGNETIC
DISTANCES IN NM
ALTITUDES AND ELEVATIONS
IN FEET

